



CP30

Construction Pup



30-ton capacity ◀ Stockpile or windrow ◀ Watertight; no leaks ◀ Low load height

800-779-8099 or 712-546-4409 • sidedump.com

CP30
Construction Pup



CP30


Construction Pup

CP30 SmithCo Side Dump Trailer

Frame Length	30' 9"
Tub Length	21'
Width	10' (120")
Loading Height	8' 4" (100")
Towing Eye	Bull Pull or Ag Hitch, 2" Drawbar Pin, 360 degree rotation
Pushblock	Standard, 24" Extensions Available
Safety Chains	1/2" Safety Chains w/ Safety Hooks
Tub Construction	1/4" Thick, AR 450 (or equivalent) Round Floor Style Tub
Frame Construction	80/100 KSI, Fabricated Steel I-Beam
Landing Gear	High Clearance
Cylinders	3500 PSI, 5" Bore
Hinges	Self-Aligning, Spherical Bearing Type (greaseable)
Suspension	90K Single Point Walking Beam
Axles	30,000# Capacity
Hubs	10 Hole, Hub Piloted
Drums	Outboard Mount, Cast Steel
Brakes	None, Hydraulic or Air Optional
Wheels	Tubeless, Steel Disc
Tires	Heavy Duty Flotation Tires
Lights	12 Volt LED ICC w/Sealed Harness
Paint	Polyurethane, any combination of gray, white or black Special colors available upon request
Min. Tractor Hydraulic Reqs.	25-30 GPM, 2,600-2,800 PSI, 10 Gallon Reservoir
Net Payload Rating	30 tons

CP30 Tub Capacities

	30-ton Tub
Waterfull	15.3 cu yd
Heaped	22 cu yd
Extended	49 cu yd (optional bolt on extensions)



Model CP30

